

Explosion-proof distribution box for motor start stop near the machine



Overview

Aluminum alloy enclosure, powder coated, corrosion-resistant and impact-resistant Stainless steel components; contact: 2A2B; current: 10A Green pushbutton (ON) and red pushbutton (OFF) Locking device is available upon request Suitable for Zone 1 and Zone 21 hazardous areas Ex d IIB+H2 T6. Aluminum alloy enclosure, powder coated, corrosion-resistant and impact-resistant Stainless steel components; contact: 2A2B; current: 10A Green pushbutton (ON) and red pushbutton (OFF) Locking device is available upon request Suitable for Zone 1 and Zone 21 hazardous areas Ex d IIB+H2 T6. Atexdelvalle offers world-class explosion-protected solutions guaranteeing highest quality and performance with no compromise. Manufacture custom made Local Control Stations & Distribution Boxes, local control panel boards and stations, explosion protected control units, distribution. *Widely used in the start and stop control conversion and display of motors in the work site, electrical parameter display during operation, speed regulation, signal switching, metering display, etc. *Different installation methods such as hanging and floor-mounted installation and different. Durable Hexlon Explosion Proof Distribution Boxes and Electrical Enclosures, IECEx and ATEX certified for Zone 1 and Zone 2. ROSE Aluminium, Polyester and Stainless-Steel Ex Enclosures and Control Stations assure reliable protection for electrical distribution systems in explosion-endangered zones.

Article Content

Power Push Button Station Box – 22mm Hole, ABS Waterproof

Its pre-drilled mounting holes and ready-made cable entry make installation simple and fast. Perfect for start/stop control, emergency stop functions, and custom automation projects, this box is ideal for

Contact Us

Continue your research online:

Website: <https://coetzerinvestments.co.za>

Technical inquiry: <https://coetzerinvestments.co.za/contact.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

